



## 221 Remington Fireball

.224"	22 Spitzer SP	22 TNT® HP
Weight (grains)	55	55
Ballistic Coefficient	0.212	0.233
Sectional Density	0.157	0.157
COAL Tested	1.830"	1.830"
Speer Part No.	1047	1032

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4227	Remington	CCI 400	14.5	2419	<b>15.4</b>	2562
IMR 4198	Remington	CCI 400	15.5	2317	<b>16.7</b>	2502
Alliant Reloder 7	Remington	CCI 400	16.4	2348	<b>17.4</b>	2501
Alliant 2400	Remington	CCI 400	12.5	2267	<b>13.5</b>	2477
Hodgdon H110	Remington	CCI 450	12.0	2250	<b>13.0</b>	2432

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*