



## 223 Remington (Handgun)

.224"	22 Spitzer SP	22 TNT® HP	22 TNT® Green®
Weight (grains)	50	50	50
Ballistic Coefficient	0.207	0.228	0.190
Sectional Density	0.142	0.142	0.142
COAL Tested	2.185"	2.250"	2.170"
Speer Part No.	1029	1030	1028

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H322	IMI	CCI 400	24.0	2749	<b>26.0</b>	3068
IMR 4895	IMI	CCI 400	25.0	2714	<b>27.0 C</b>	3037
Accurate 2520	IMI	CCI 450	26.0	2848	<b>28.0 C</b>	3030
IMR 3031	IMI	CCI 400	24.0	2571	<b>26.0 C</b>	2960
Winchester 748	IMI	CCI 450	26.0	2728	<b>28.0</b>	2954
Hodgdon H4895	IMI	CCI 400	23.5	2537	<b>25.5 C</b>	2917
Vihtavuori N133	IMI	CCI 400	22.0	2638	<b>24.0</b>	2900
Accurate 2015	IMI	CCI 400	22.5	2651	<b>24.5</b>	2890
IMR 4198	IMI	CCI 400	20.0	2608	<b>22.0</b>	2870

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*