



25 Automatic

.251"	25
Weight (grains)	GDHP
Ballistic Coefficient	35
Sectional Density	0.091
COAL Tested	0.079
Speer Part No.	0.870"
	3985

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Bullseye	Speer	CCI 500	DNR	—	1.7	1040
Hodgdon TITEGROUP	Speer	CCI 500	DNR	—	1.7	1008
Accurate No. 2 Improved	Speer	CCI 500	DNR	—	1.8	1004
Hodgdon Hi-Skor 700-X	Speer	CCI 500	DNR	—	1.7	971
Alliant Red Dot	Speer	CCI 500	DNR	—	1.5	966
Winchester 231	Speer	CCI 500	DNR	—	1.7	937

DNR — do not reduce

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load