



32-20 Winchester (Contender Only)

.308"	30 HP	30 SPFN Hot- Cor®
Weight (grains)	130	130
Ballistic Coefficient	0.244	0.213
Sectional Density	0.196	0.196
COAL Tested	1.910"	1.865"
Speer Part No.	2005	2007

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Winchester	CCI 500	14.0	1479	15.0	1664
IMR 4227	Winchester	CCI 500	14.5	1479	15.5 C	1645
Accurate No. 9	Winchester	CCI 500	12.0	1476	13.0	1632
Winchester 296	Winchester	CCI 500	13.5	1443	14.5	1602
IMR SR 4759	Winchester	CCI 500	12.0	1256	13.0	1489
Alliant 2400	Winchester	CCI 500	10.5	1234	11.5	1488
IMR 4198	Winchester	CCI 500	15.0	1339	16.0 C	1453
Alliant Herco	Winchester	CCI 500	6.8	1270	7.8	1387
Hodgdon HS-6	Winchester	CCI 500	7.6	1246	8.6	1340

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load