



10mm Auto

.400"	40 GDHP	40 TMJ® FN
Weight (grains)	165	165
Ballistic Coefficient	0.138	0.135
Sectional Density	0.147	0.147
COAL Tested	1.255"	1.255"
Speer Part No.	4397	4410

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate No. 9	Hornady	CCI 350	14.5	1277	15.5	1344
Alliant Power Pistol	Hornady	CCI 300	9.0	1204	10.0	1314
Accurate No. 7	Hornady	CCI 300	11.2	1177	12.2	1278
Alliant Blue Dot	Hornady	CCI 300	10.5	1181	11.5	1273
Alliant 2400	Hornady	CCI 300	13.8	1159	14.8	1234
Vihtavuori 3N37	Hornady	CCI 300	8.3	1091	9.2	1228
Hodgdon H. Universal	Hornady	CCI 300	6.8	1100	7.5	1205
Alliant Unique	Hornady	CCI 300	7.4	1126	8.3	1194
Hodgdon HS-6	Hornady	CCI 350	9.0	1071	10.0	1185
Winchester WSF	Hornady	CCI 300	7.2	1065	8.0	1177
Winchester 231	Hornady	CCI 300	6.3	1043	7.0	1143

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*