



## 10mm Auto

.400"	40 TMJ® FN	40 GDHP
Weight (grains)	180	180
Ballistic Coefficient	0.143	0.143
Sectional Density	0.161	0.161
COAL Tested	1.250"	1.250"
Speer Part No.	4402	4406

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Blue Dot	Hornady	CCI 300	10.0	1105	<b>11.0</b>	1295
Alliant 2400	Hornady	CCI 300	11.5	1051	<b>12.8</b>	1214
Accurate No. 7	Hornady	CCI 300	11.0	1065	<b>12.0</b>	1180
Vihtavuori N350	Hornady	CCI 300	8.9	1077	<b>9.7</b>	1152
Vihtavuori 3N37	Hornady	CCI 300	9.0	1027	<b>10.0</b>	1150
Alliant Unique	Hornady	CCI 300	7.2	1043	<b>8.0</b>	1138
Winchester WSF	Hornady	CCI 300	6.8	1001	<b>7.5</b>	1120
Accurate No. 5	Hornady	CCI 300	8.5	1015	<b>9.5</b>	1116
Hodgdon HS-6	Hornady	CCI 350	8.2	1001	<b>9.1</b>	1099

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*