



41 Remington Magnum

.410"	41
Weight (grains)	210
Ballistic Coefficient	0.183
Sectional Density	0.178
COAL Tested	1.575"
Speer Part No.	4430

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 300-MP	Federal	CCI 350	21.2	1216	23.6	1369
Winchester 296	Winchester	CCI 350	20.5	1251	21.5	1295
Hodgdon H110	Winchester	CCI 350	20.5	1237	21.5	1265
Accurate No. 9	Winchester	CCI 300	17.0	1199	18.0	1265
Vihtavuori N110	Winchester	CCI 300	17.0	1136	18.0	1244
Alliant Power Pistol	Federal	CCI 350	10.8	1167	11.6	1228
Alliant 2400	Winchester	CCI 300	18.0	1176	19.0	1223
Alliant BE-86	Federal	CCI 350	10.1	1171	10.8	1221
IMR 4227	Winchester	CCI 300	21.0	1117	22.0	1203
Winchester AutoComp	Federal	CCI 350	9.2	1054	10.2	1158
Hodgdon CFE Pistol	Federal	CCI 350	9.0	1054	9.9	1155
Alliant Unique	Winchester	CCI 300	8.7	1034	9.7	1123
Vihtavuori N350	Winchester	CCI 300	9.8	1035	10.5	1110

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load