



44 Remington Magnum

.429"	44
	Special GDHP SB
Weight (grains)	200
Ballistic Coefficient	0.145
Sectional Density	0.115
COAL Tested	1.610"
Speer Part No.	4427

SHORT BARREL VELOCITIES
 Test Firearm: S&W M29 4"
 Note: these loads do not produce maximum pressure.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H. Universal	Speer	CCI 300	8.9	999	10.0	1132
Alliant Unique	Speer	CCI 300	9.0	990	11.0	1122
Alliant American Select	Speer	CCI 300	8.6	1005	10.0	1120
Hodgdon Hi-Skor 700-X	Speer	CCI 300	7.9	997	9.0	1109
Alliant Red Dot	Speer	CCI 300	8.2	1033	9.2	1096
Hodgdon TITEGROUP	Speer	CCI 300	7.9	989	9.0	1084
Winchester 231	Speer	CCI 300	8.9	989	10.0	1083
Alliant Bullseye	Speer	CCI 300	8.0	1014	9.0	1080

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load