



45 Colt

.451"	45 GDHP SB	45 GDHP
Weight (grains)	230	230
Ballistic Coefficient	0.148	0.143
Sectional Density	0.162	0.162
COAL Tested	1.600"	1.600"
Speer Part No.	4482	4483

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Blue Dot	Winchester	CCI 300	12.0	967	13.0	1036
IMR SR 4756	Winchester	CCI 300	10.3	836	11.0	962
Vihavuori N110	Winchester	CCI 300	16.0	778	18.0	946
Hodgdon HS-6	Winchester	CCI 350	10.8	876	11.8	936
Alliant Unique	Winchester	CCI 300	8.1	827	9.0	932
Alliant Herco	Winchester	CCI 300	8.4	839	9.4	918
Accurate No. 5	Winchester	CCI 300	10.8	840	11.8	912
Alliant Bullseye	Winchester	CCI 300	6.4	825	7.1	890
Alliant Power Pistol	Winchester	CCI 300	8.5	823	9.5	878
Hodgdon H. Universal	Winchester	CCI 300	8.2	819	9.0	873
Winchester 231	Winchester	CCI 300	7.5	804	8.3	870

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load