



460 Smith & Wesson Magnum

.451"	45
	JSP
Weight (grains)	300
Ballistic Coefficient	0.199
Sectional Density	0.211
COAL Tested	2.170"
Speer Part No.	4485

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 1680	Hornady	Federal 210	42.0	1478	44.0	1591
Alliant 2400	Hornady	Federal 210	28.0	1392	30.0	1550
Hodgdon H. Lil' Gun	Hornady	Federal 210	29.0	1464	31.0	1544
Accurate No. 9	Hornady	Federal 210	25.0	1420	27.0	1527
Ramshot Enforcer	Hornady	Federal 210	30.0	1457	32.0	1515
Hodgdon H110	Hornady	Federal 210	29.0	1406	31.0	1475
IMR 4227	Hornady	Federal 210	33.0	1375	35.0	1471
Winchester 296	Hornady	Federal 210	32.0	1504	34.0	1469
Vihtavuori N110	Hornady	Federal 210	29.0	1394	31.0	1458
Alliant Power Pistol	Hornady	Federal 210	18.0	1292	20.0	1359
Alliant BE-86	Hornady	Federal 210	15.6	1102	17.7	1269
Hodgdon CFE Pistol	Hornady	Federal 210	15.1	1073	17.1	1184

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load